

TECHNICAL HEALTH AND DATA SHEET

PRODUCT:- GLOCOTE FLUORESCENT PAINT

REFERENCE:- D/125/

COLOUR:- ORANGE, PINK, YELLOW, GREEN, RED

FINISH:- MATT

TYPE:- ALKYD BASED

TYPICAL SG:- 1.12 @ 20°C

TYPICAL VISCOSITY:- 3.5 POISE @ 25°C

TYPICAL TOTAL SOLIDS:- 56.4% BY WEIGHT

FLASH POINT:- ABOVE 32°C

RECOMMENDED THINNERS:- WHITE SPIRIT OR TURPS.SUBS.
V/607/14

APPLICATION:- BY BRUSH OR SPRAY. MUST BE
APPLIED OVER HIGH DENSITY WHITE
FOUNDATION COATING F/158/1 FOR
MAXIMUM REFLECTANCE.

*COVERAGE GUIDE:- 8 SQ. METRES/LITRE

*DRYING TIME:- SURFACE DRY - 3 HOURS
THROUGH DRY - 12 HOURS

USES:- A HIGH VISIBILITY DAYLIGHT COATING
FOR SAFETY SIGNS AND HAZARDOUS
OBJECTS. FOR INCREASED EXTERNAL
DURABILITY, A CLEAR PROTECTIVE,
V601/27 IS RECOMMENDED.

HEALTH & SAFETY:- SEE SHEET HSD 'A'

*BY BRUSH TO A DRIED FILM THICKNESS OF 20-25 MICRONS AT 20°C.

TECHNICAL HEALTH AND DATA SHEET

PRODUCT:- FOUNDATION BASE

REFERENCE:- F/158/1

COLOUR:- WHITE

FINISH:- MATT

TYPE:- MODIFIED ALKYD

TYPICAL S.G.: - 1.41 @ 20°C

TYPICAL VISCOSITY:- 3.5 POISE @ 25°C

TYPICAL TOTAL SOLIDS:- 66.2% BY WEIGHT
40.0% BY VOLUME

FLASH POINT:- ABOVE 32°C

RECOMMENDED THINNERS:- WHITE SPIRIT OR TURPS. SUBS.

RECOMMENDED APPLICATION:- BRUSH, ROLLER OR SPRAY

*COVERAGE GUIDE:- 10 SQ. METRES/LITRE

*DRYING TIME:- 2 HOURS SURFACE DRY
12 HOURS THROUGH DRY

*BY BRUSH TO A DRIED FILM THICKNESS OF 20-25 MICRONS AT 20°C

TECHNICAL HEALTH AND DATA SHEET

PRODUCT:- FLUORESCENT & LUMINOUS
PROTECTIVE COATING

REFERENCE:- V/601/27

COLOUR:- CLEAR

FINISH:- FULL GLOSS

TYPE:- MODIFIED ALKYD

TYPICAL SG:- 0.92 @ 20°C

TYPICAL VISCOSITY:- 2.5 POISE @ 25°C

TYPICAL TOTAL SOLIDS:- 54.0% BY WEIGHT

FLASH POINT:- ABOVE 32°C

RECOMMENDED THINNERS:- WHITE SPIRIT (TURPS. SUBS)

RECOMMENDED APPLICATION:- BY BRUSH

*COVERAGE GUIDE:- 14 SQ. METRES/LITRE

*DRYING TIME:- TOUCH DRY - 4-6 HOURS
THROUGH DRY - 24 HOURS

USES:- AS A HIGH BUILD FINISH FOR USE
AS A SEALER FOR FLUORESCENT
AND LUMINOUS PAINT. CAN ALSO
BE USED AS A VARNISH TO GIVE
PROTECTION & HIGHER GLOSS TO
EXISTING PAINTWORK.

HEALTH & SAFETY DATA:- HSD SHEET 'A'

*BY BRUSH TO A DRIED FILM THICKNESS OF 15-20 MICRONS @ 20°C.

C1.

SAFETY DATA SHEET

Product:- GLOCOTE FLUORESCENT PAINT D/125

Date of issue:- 24/10/94 Issue No 1

Page 1 Of 7

1. IDENTIFICATION OF THIS PREPARATION.

Product name:- GLOCOTE

Intended use:- FLUORESCENT PAINT

Company:- COO-VAR

LOCKWOOD STREET

HULL HU2 OHN

Telephone:- 0482 28053 Fax:- 0482 219266

Emergency contact:- as above.

2. COMPOSITION/INFORMATION ON INGREDIENTS.

Substances presenting a health hazard within the meaning of the Chemicals (Hazard Information and Packaging) Regulations 1993.

<u>NAME</u>	<u>CONC.RANGE%</u>	<u>SYMBOL LETTER</u>	<u>R-PHRASES*</u>
White spirit	25-50	NONE	10

*for full text see section 16

3. HAZARDS IDENTIFICATION

The product is not classified as dangerous according to the Chemicals (Hazard Information and Packaging) Regulations. (also refer to Section 11)

4. FIRST AID MEASURES

GENERAL:

In all cases of doubt, or when symptoms persist, seek medical attention.

Never give anything by mouth to an unconscious person.

INHALATION:

Remove to fresh air, keep the patient warm and at rest.

If breathing is irregular or stopped, administer artificial respiration, Give nothing by mouth. If unconscious, place in the recovery position and seek medical advice.

EYE CONTACT:

Contact lenses should be removed. Irrigate copiously with clear, fresh water for at least 10 minutes, holding the eyelids apart, and seek medical advice.

SKIN CONTACT:

Remove contaminated clothing. Wash skin thoroughly with soap and water or use a proprietary skin cleaner. DO NOT use solvents or thinners.

INGESTION:

If accidentally swallowed obtain immediate medical attention. Keep at rest. DO NOT induce vomiting.

5. FIRE FIGHTING MEASURES.

EXTINGUISHING MEDIA:

Recommended:- Alcohol-resistant foam, CO₂, powder, water spray/mist.

Not to be used:- water jet.

RECOMMENDATIONS:

Fire will produce dense black smoke containing hazardous products of combustion (see Section 10). Decomposition products may be a hazard to health. Appropriate self-contained breathing apparatus may be required. Cool closed containers exposed to fire with water spray. Do not allow run-off from fire fighting to enter drains or water courses.

6. ACCIDENTAL RELEASE MEASURES.

Exclude non-essential personnel. Avoid breathing vapours. Refer to protective measures listed in Section 7 and 8.

Contain and collect spillages with non-combustible materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for disposal in accordance with the waste regulations (see Section 13). Do not allow to enter drains or water courses.

Clean preferably with a detergent; avoid the use of solvents.

If the product enters drains or sewers the local water company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the National Rivers Authority.

7. HANDLING AND STORAGE

HANDLING:

Prevent air-borne concentrations higher than the occupational exposure limits. Keep the container tightly closed. Exclude sources of heat, sparks and open flames. Avoid skin and eye contact. Avoid inhalation of vapour (and spray mist) smoking, eating and drinking should be prohibited in areas of storage and use. For personal protection, see Section 8. Never use pressure to empty; the container is not a pressure vessel. Always keep in containers made of the same material as the supply container. Good housekeeping standards and regular safe removal of waste materials will minimise risks of spontaneous combustion and other fire hazards. The Manual Handling Operations Regulations may apply to the handling of containers of this product.

Product: D/125

Date of Issue: 24/10/94 Issue No 1

Page 3 of 7

STORAGE:

Observe the label precautions. Store between 5 and 25°C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Prevent unauthorised access. Containers which are opened should be properly resealed and kept upright to prevent leakage. Store separately from oxidising agents and strongly alkaline and strongly acidic materials.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION.

ENGINEERING MEASURES.

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and/ or solvent vapours below the relevant occupational exposure limits, suitable respiratory protective equipment should be worn. (see "Personal Protection" below)

EXPOSURE LIMITS

OCCUPATIONAL EXPOSURE LIMITS.

SUBSTANCE	8Hr TWA ⁽¹⁾	10MIN STEL ⁽²⁾
White Spirit	100 ppm (575 mg/m)	125 ppm (725 mg/m)

Notes:

- (1) Long term exposure limit- 8 hour time weighted average.
- (2) Short term exposure limit - 10 minute reference period.
OELs are taken from the current version of EH 40.

PERSONAL PROTECTION.

All PPE, including RPE, used to control exposure to hazardous substances must be selected to meet the requirements of the COSHH Regulations.

RESPIRATORY PROTECTION:

If exposure to hazardous substances identified above cannot be controlled by the provision of local exhaust ventilation and good general extraction, suitable respiratory equipment should be worn.

HAND PROTECTION:

When skin exposure may occur, advice should be sought from glove suppliers on appropriate types. Barrier creams may help to protect exposed areas of the skin but are not substitutes for full physical protection. They should not be applied once exposure has occurred.

EYE PROTECTION:

Eye protection designed to protect against liquid splashes should be worn.

SKIN PROTECTION:

Cotton or cotton/synthetic overalls or coveralls are normally suitable. Grossly contaminated clothing should be removed and the skin washed with soap and water or a proprietary skin cleaner.

9. PHYSICAL AND CHEMICAL PROPERTIES.

Physical state: Brightly coloured Viscous Liquids.
Flash point: 38°C approximately (closed cup)
Viscosity: 3.5 poise at 25°C (Rotothinner)
Specific gravity: 1.12 approximately at 20°C
Vapour density: heavier than air
Lower explosion limit: 0.8%
Solubility in water: insoluble

10. STABILITY AND REACTIVITY

Stable under the recommended storage and handling conditions. (See Section 7).
In a fire, hazardous decomposition products such as smoke, carbon monoxide, carbon dioxide and oxides of nitrogen may be produced. Keep away from oxidising agents and strongly acidic materials to prevent the possibility of exothermic reaction.

11. TOXICOLOGICAL INFORMATION

There is no data available on the product itself. (Exposure to organic solvent vapours may result in adverse health effects such as irritation of the mucous membrane and the respiratory system and adverse effects on the renal and central nervous systems. Symptoms include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Repeated or prolonged contact with the product may lead to removal of natural fats from the skin resulting in non-allergic contact dermatitis and absorption through the skin. Splashes in the eyes may cause irritation and reversible local damage.

12. ECOLOGICAL INFORMATION

There is no data available on the product itself. The product should not be allowed to enter drains or water courses or be deposited where it can affect ground or surface waters.

The Air Pollution Control requirements of regulations made under the Environmental Protection Act may apply to the use of this product.

13. DISPOSAL CONSIDERATIONS.

Do not allow into drains or water courses or dispose of where ground or surface waters may be affected. Wastes, including emptied containers, are controlled wastes and should be disposed of in accordance with regulations made under the Control of Pollution Act and the Environmental Protection Act.

(Using the information provided in this safety data sheet, advice should be obtained from the Waste Regulation Authority whether the special waste regulations apply).

14. TRANSPORT INFORMATION.

UK ROAD/RAIL CLASSIFICATION: FLAMMABLE LIQUID SI NUMBER 1263
PACKING GROUP: 111

I.M.O. CLASS 3.3 PACKING GROUP 111 UN NUMBER 1263
MARINE POLLUTANTS - YES

15. REGULATORY INFORMATION.

The product is determined as not being dangerous according to the chemicals (Hazard Information and Packaging) Regulations.

The information contained in the safety data sheet does not constitute the user's own assessments of workplace risks as required by other health and safety legislation. The provisions of the Health and Safety at Work etc. Act and the Control of Substances Hazardous to Health Regulations apply to the use of this product at work.

16. OTHER INFORMATION.

Text of R-Phrase listed in Section 2: R10- FLAMMABLE. This safety data sheet is provided in accordance with the provisions of Section 6 of the Health and Safety at Work, etc ACT 1974, as amended by the Consumer Protection Act 1987.

The product should not be used for purposes other than shown in Section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.

Product: D/125

Date of Issue: 24/10/94 Issue No 1

Page 7 of 7

The information contained in this safety data sheet is based on the present state of knowledge and current national legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

Further information and relevant advice can be found in:-

The Control of Substances Hazardous to Health
Regulations 1988 (SI 1988:1657)

The Manual Handling Operations Regulations 1992
(SI 1992:2793)

The Environmental Protection (Duty of Care)
Regulations 1992 (SI 1992:2839)
